

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/IL04/001128

International filing date: 14 December 2004 (14.12.2004)

Document type: Certified copy of priority document

Document details: Country/Office: IL  
Number: 159406  
Filing date: 16 December 2003 (16.12.2003)

Date of receipt at the International Bureau: 21 February 2005 (21.02.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse





מדינת ישראל  
STATE OF ISRAEL

Ministry of Justice  
Patent Office

משרד המשפטים  
לשכת הפטנטים

This is to certify that  
annexed hereto is a true  
copy of the documents as  
originally deposited with  
the patent application  
particulars of which are  
specified on the first page  
of the annex.

זאת לתעודה כי  
רצופים בזה העתקים  
נכונים של המסמכים  
שהופקדו לכתחילה  
עם הבקשה לפטנט  
לפי הפרטים הרשומים  
בעמוד הראשון של  
הנספח.



Commissioner of Patents

נתאשר  
Certified

לשימוש הלשכה  
For Office Use

חוק הפטנטים, התשכ"ז - 1967  
PATENTS LAW, 5727 - 1967

**בקשה לפטנט**

Application for Patent

**159406**

מספר:  
Number

תאריך:  
Date

**16-12-2003**

הוקדם/נדחה  
Ante/Post-dated

**אנו/י,** (שם המבקש, מענו ולגבי גוף מאוגד - מקום התאגדותו)

**We/I,** (Name and address of applicant, and in case of body corporate - place of incorporation)

NUCLEAR RESEARCH CENTER

Nahal Soreq

Yavne 81800

המרכז למחקר גרעיני

נחל שורק

יבנה 81800

Inventor: **Mark Goldberg**

ממציא: **מרק גולדברג**

בעל אמצאה מכח הדין ששמה הוא

Owner, by virtue of being the inventor of an invention the title of which is

**שיטה ומערכת לגילוי חומרים, כגון חומרים גרעיניים מיוחדים**

(בעברית)

(Hebrew)

**METHOD AND SYSTEM FOR DETECTING SUBSTANCES, SUCH AS SPECIAL NUCLEAR MATERIALS**

(באנגלית)

(English)

*בקשת חלוקה - Application of Division		*בקשת פטנט מוסף - Application for Patent Addition		דרישה דין קדימה Priority Claim	
*מבקשת פטנט from Application		*לבקשה/לפטנט to Patent/Appl.		מספר/סימן Number/Mark	מדינת האגוד Convention Country
מס'..... dated.....		מס'..... dated.....		תאריך Date	
POA:		יפוי-כח:			
הוגש בעניין בקשה 153523 המען למסירת מסמכים בישראל Address for Service in Israel					
דקל פטנט בע"מ בית הרופאים מנוחה ונחלה 18, חדר 27, רחובות 76209					
Signature of the Applicant		חתימת המבקש		היום 16_12_2003 שנת 2003 This 16 of December 2003	
For the Applicant, דוד קליין, ע"פ דקל פטנט בע"מ בית הרופאים מנוחה ונחלה 18, חדר 27, רחובות 76209		עבור המבקש,		לשימוש הלשכה For Office Use	
DATE: 16.12.03		תאריך:			
REFERENCE: 1384MMG-IL		סימוכין:			

טופס זה, כשהוא מוטבע בחותם לשכת הפטנטים ומושלים במספר ובתאריך ההגשה, הנו אישור להגשת הבקשה שפרטיה רשומים לעיל.

This form, impressed with the Seal of the Patent Office and indicating the number and date of filing, certifies the filing of the application the particulars of which are set out above.

\*מחק את המיותר Delete whatever is inapplicable

שיטה ומערכת לגילוי חומרים, כגון חומרים גרעיניים מיוחדים

**METHOD AND SYSTEM FOR DETECTING SUBSTANCES, SUCH AS SPECIAL  
NUCLEAR MATERIALS**

1384MMG-IL

## METHOD AND SYSTEM FOR DETECTING SUBSTANCES, SUCH AS SPECIAL NUCLEAR MATERIALS

### FIELD OF THE INVENTION

The present invention relates generally to methods and systems for detecting small amounts of special nuclear materials (SNM) hidden in cargo and vehicles.

### BACKGROUND OF THE INVENTION

In recent years, ever-higher priority is being accorded to developing state-of-the-art security-screening techniques and devices that will reliably and rapidly detect small quantities (tens of grams) of SNM concealed within cargo and vehicles.

The following are examples of the prior art:

**a) Passive radiation-monitoring systems:**

Such "Portal Monitors" were developed for the purpose of interdicting theft or diversion of SNM from high-security sites. The detection of SNM is based on measuring an increase in radiation intensity above the ambient background. Among others, LANL (Los Alamos National Laboratories) and LLNL (Lawrence Livermore National Laboratories) have been active in developing such systems, which are usually packaged in three distinct categories: 1) Small, Hand-Held Monitors 2) Automatic Pedestrian Monitors 3) Automatic Vehicle Monitors.

Vehicle monitoring systems for detecting SNM are now available from several commercial companies. Among these, Canberra's **JPM-12A** Vehicle Monitor was developed jointly with LANL. It consists of two large plastic scintillators positioned on either side of the portal, that measure the gamma-rays emitted from SNM. The instrument can detect **10 gr** of **Pu** and **1000 gr** of HEU in an unshielded vehicle moving at a speed of **2 m/s**. The disadvantage of this method is that gamma detection can be thwarted with relative ease by enveloping the SNM with **Pb**-sheet, since the minimum detected quantities increase rapidly by an order of magnitude when shielded by several mm of it. In the **Pu** case, the problem can be countered by using neutron detectors in the portal. However, due to low neutron emission rates, this approach requires large-area neutron detectors. LANL has developed such a system, based on two large-area <sup>3</sup>He detectors between which vehicles pass. An equivalent system is currently marketed by TSA-Systems-Ltd., Model NVM-245. NUCSAFE's Vehicle Monitor claims detection of **5 gr**

of gamma-shielded weapons-grade **Pu** within **10 s** at **1 m** distance. Also available are gamma-neutron Vehicle Portal Monitors manufactured by LAURUS-Systems-Inc. Model No. VM-250GN and by POLIMASTER, Model Series PM5000. For the latter, which incorporate sizeable plastic-scintillator detectors as well as large-area  $^3\text{He}$  proportional counters, detection of **4.3 gr  $^{239}\text{Pu}$**  and **300gr  $^{235}\text{U}$**  at a scan speed of **10 km/hr** is claimed. However, in analogy to  $\gamma$ -rays, small **Pu** quantities might evade detection if some neutron shielding is introduced.

#### **b) Single-energy radiography systems**

This method yields information about the contents of the screened object. A number of systems have been developed in recent years by commercial companies. Nearly all of them use high energy bremsstrahlung radiation produced by high-power linacs, although SAIC have built a line of products (VACIS) around a radioactive  $^{60}\text{Co}$  source. In several systems, two views at  $90^\circ$  to each other are generated, to obtain more information. Commercial companies such as Smiths-Heimann and Aracor produce linac-based vehicle and marine container inspection systems. They operate at electron energies of  $\sim 10 \text{ MeV}$  and employ Cadmium-Tungstate radiation detectors. The spatial resolution permits the detection of **1 mm** copper wire. The scan time is  $\sim 3$  minutes for a **20 m**-long vehicle, but the visual inspection time of the resulting image typically takes **10-15** minutes. These systems penetrate  $\sim 30 \text{ cm}$  of steel and the radiation dose to the object is about **150-250  $\mu\text{Gy}$** . Their obvious drawback is that they do not automatically identify SNM and in general, the performance of such systems relies heavily on operator skill and judgment.

#### **c) Dual-energy radiography (DER) systems**

DER is a well-established technique that has found numerous applications in medical imaging (in particular, in-vivo bone mineral densitometry), environmental studies, material assaying, NDT, NDE, as well as security inspection scenarios. They are based on comparing the transmission attenuation at two energies, a sensitive measure for the atomic number **Z** of the absorbers in the line-of-sight from radiation source to detector.

DER scans are usually performed at energies where the photoelectric component of the transmission attenuation dominates. One particular variant exploits characteristic discontinuities in attenuation when the incident photon energy is varied around inner-atomic-shell (**K,L,M,...**) binding energies of a particular element. Typically, the latter vary with  $\text{Z}^2$ . Locating such an energy-discontinuity (by comparing the photon flux

transmission above and below it) is a sensitive indication of the presence of the element in question in the field-of-view. However, this variant of the method is unsuitable for inspecting massive cargo items such as aviation or marine containers, since the relevant K-binding energies (the highest-energy discontinuities) for  $Z \sim 92$  are at  $\sim 110$  keV, an energy too low to penetrate the inspected items.

In summary, the inadequacy of existing screening methods to effectively interdict the illicit-transport of SNM at the crucial outgoing and incoming control points underscores the need for novel inspection systems that will reliably detect the presence of small quantities of SNM in cargo items ranging in magnitude from small packages, through passenger baggage, palletized cargo and aviation containers, up to a full-size marine container, loaded land-vehicle or railroad freight-car.

### SUMMARY OF THE INVENTION

The present work describes a novel and sensitive method for detecting small quantities of special nuclear materials (SNM) concealed in packages, passenger baggage, massive cargo and vehicles. It is based on dual-energy radiography (DER) of  $\gamma$ -rays, whereby the pair-production-related increase in transmission attenuation with photon energy characteristic of high- $Z$  materials is exploited to detect and distinguish them from the low- $Z$  and medium- $Z$  substances that make up the overwhelming majority of benign transported items. Moreover, it is possible to differentiate between threat materials and other, benign high- $Z$  substances of lower density, such as Hg, Pb or Bi, provided at least two DER projections are taken. In order to construct a practicable system with good performance characteristics, judicious choices of  $\gamma$ -ray energies and populating reactions employing low-energy ion beams at sub-mA intensities are preferable. To this end, a comprehensive literature study of reaction-induced  $\gamma$ -ray yields has been performed, providing best-mode radiation sources, although the invention is not limited to these radiation sources. These are the  $^{12}\text{C}$  lines at 4.43 MeV & 15.09 MeV populated, in decreasing yield order, by the  $^{11}\text{B}(\text{d},\text{n})$ ,  $^{13}\text{C}(\text{}^3\text{He},\alpha)$  &  $^{10}\text{B}(\text{}^3\text{He},\text{p})$  reactions at energies  $E_{\text{beam}} < 5$  MeV. An alternative option is presented by the  $^{11}\text{B}(\text{p},\gamma)$  reaction, for which  $E_{\text{p}} \sim 9$  MeV may be needed to fully exploit the giant-dipole-resonance  $\gamma$ -rays at 16-24 MeV. The yield of the latter reaction is lower than that of d-induced and  $^3\text{He}$ -induced reactions, but it may give rise to superior image contrast sensitivity, the upper DER gamma-ray energy being higher. The best-suited detectors may be organic scintillators with pulse-

shape-discrimination (PSD) properties. As shown by a preliminary simulation, an operational DER inspection system built around such components may enable reliable detection of small (tens of gr) SNM quantities within short scanning times (typically, a few minutes), even in massive cargo items and loaded vehicles that exhibit high image clutter. Typical absorbed radiation doses to inspected items would be in the acceptable range of (1-10)  $\mu\text{Gy}$ .

There is thus provided in accordance with an embodiment of the present invention a method for detecting substances, the method including performing multi-view, multi-energy radiography by irradiating an object with a plurality of discrete high-energy gamma-rays at a plurality of different orientations, and detecting and mapping radiation passing through the object with at least one array of detectors, and indicating a presence of a high- $Z$  substance (e.g., a special nuclear material (SNM)), by detecting a difference in a transmission attenuation characteristic of the high- $Z$  substance as opposed to low- $Z$  and medium- $Z$  substances.

The method may also include determining and localizing regions within the object containing the high- $Z$  substance (or high density substance) with the multi-view, multi-energy radiography, in order to enhance specificity to SNM, as opposed to other high- $Z$  materials

There is also provided in accordance with an embodiment of the present invention a system for detecting substances, the system including a dual-energy radiography (DER) system including a gamma-ray radiation source, including a beam accelerator and a target to which the accelerator sends a beam thereby producing gamma rays, and a plurality of gamma ray detectors positioned to detect gamma ray beams that pass from the gamma-ray radiation source through an object to be inspected, wherein the DER system is adapted to indicate a presence of a high- $Z$  substance, by detecting a difference in a transmission attenuation characteristic of the high- $Z$  substance as opposed to low- $Z$  and medium- $Z$  substances.

The DER system may make two measurements of transmission attenuation characteristics, one measurement performed at a photon energy close to the global absorption minimum for all atomic numbers  $Z$  (at  $\sim 4 \text{ MeV}$ ) and another at a higher photon energy.



## BRIEF DESCRIPTION OF DRAWINGS

In the drawings:

Fig. 1 is a simplified graph of values of  $\Delta\mu$  as a function of  $Z$  for various photon energies, relative to 4.43 MeV, the abscissa being the atomic number  $Z$ , and the ordinate,  $\Delta\mu$  in  $\text{cm}^2/\text{g}$ .

Fig. 2 is a simplified graph of  $\Delta\mu \cdot \rho$ , the difference in macroscopic attenuation coefficient calculated for  $E_{\gamma\text{high}} = 15.09$  MeV and  $E_{\gamma\text{low}} = 4.43$  MeV at the stable high- $Z$  elements, beginning with the last rare earth (Hf), using nominal bulk densities, the abscissa being the atomic number  $Z$ , and the ordinate,  $\Delta\mu \cdot \rho$  in  $1/\text{cm}$ .

Fig. 3 is a simplified graph of the systematics of ground-state  $Q$ -values for  $p$ -capture reactions on light nuclei, the abscissa being the target mass number  $A$ , and the ordinate,  $Q_0$  in MeV.

Fig. 4 is a simplified level scheme of  $^{12}\text{C}$  showing the states of interest, along with various reactions that feed and de-excite them. The  $^{11}\text{B}(p,\gamma)$  excitation curve is shown alongside the corresponding states, clearly showing the giant dipole resonances that decay to the ground-state and to the 1<sup>st</sup> excited state. Also shown are the low-lying states of  $^{12}\text{B}$  fed in  $^{11}\text{B}(d,p)$  and their decay modes.

Fig. 5 is a simplified graph of measured thick-target yields per projectile of reactions generating high-energy  $^{12}\text{C}$   $\gamma$ -rays, the abscissa being  $E_{\text{projectile}}$  in MeV, and the ordinate, the yield ( $\times 10^{-9}$ ). The yellow (labeled Y) and magenta (labeled M) curves both pertain to the  $p$ -capture reaction, but the yields refer to gamma-rays leading to the 1<sup>st</sup> excited state & ground state, respectively. The energies differ by 4.43 MeV and vary with incident proton energy as indicated near the curves themselves. The yield increase above  $\sim 5$  MeV is due to the giant dipole resonance. The blue (labeled B) and green (labeled G) curves refer to the 15.09 MeV yields from reactions with  $^3\text{He}$  beams, of varying yield and spectral cleanliness, as indicated near the curves. The red curve (labeled R) represents the 15.09 MeV yield from the  $(d,n)$  reaction on a  $^{11}\text{B}$  target. Apart from the effects of neutrons, these gamma-spectra (see Figs. 6 and 7) are remarkably clean. For comparison, the black circle indicates the 9.17 MeV gamma-yield of  $p$ -capture on  $^{13}\text{C}$ .

Fig. 6 is a simplified graph of an in-beam **NaI** gamma-ray spectrum from bombardment of a  $^{11}\text{B}$  target with a 2.75 MeV deuteron beam, the abscissa being the channel number and the ordinate, the relative intensity.

Fig. 7 is a simplified graph of an in-beam germanium gamma-ray spectrum from bombardment of a deuterium target with a 19.1 MeV  $^{11}\text{B}$ -beam, the abscissa being  $E_\gamma$  in MeV, and the ordinate, the number of counts. The equivalent d-beam energy is 3.47 MeV.

Fig. 8 is a simplified schematic outline of a DER screening system, constructed and operative in accordance with an embodiment of the present invention, in the plane of the d-beam and central  $\gamma$ -detector.

## DETAILED DESCRIPTION OF EMBODIMENTS

### Dual-Energy Radiography In The Present Scenario – Basic Physics

In view of the fundamental limitations of existing screening equipment described in the previous section, recourse may be made to characteristic features of the attenuation process that come into play at higher photon energies (in the 1-30 MeV range), for which the radiation is much more penetrating. In this photon energy range, the pair-production attenuation mechanism comes into play, so that the total attenuation coefficient exhibits a rise above ~4 MeV, which is progressively more pronounced as the  $Z$  of the absorber increases. Thus, in order to distinguish between high- $Z$  materials and lighter elements, one measurement may be performed at the global absorption minimum for all atomic numbers  $Z$  (at ~4 MeV) and another at higher energy. This is the basis for SNM detection underlying the present work.

Specifically, the intensity-fraction transmitted through two absorbers of atomic number  $Z_a$ ,  $Z_b$  at each of two different photon energies  $E_{\gamma 1}$  &  $E_{\gamma 2}$  is given by the expression:

$$T(E_{\gamma i}) = e^{-(\mu_{a_i} \cdot \rho_a \cdot x_a + \mu_{b_i} \cdot \rho_b \cdot x_b)}, \quad i=1,2 \quad \text{eq. (1)}$$

where  $\rho$ ,  $\mu$  &  $x$  are the density, specific attenuation coefficient and thickness in the line-of sight from source to detector, for absorbers **a** & **b**, respectively. The coefficients  $\mu$  are characteristic and known functions of both  $Z$  and  $E_\gamma$ .

It follows from eq. (1) that the *Transmission Ratio* at the two energies is given by:

$$T(E_{\gamma 1}) / T(E_{\gamma 2}) = e^{-(\Delta\mu_a \cdot \rho_a \cdot x_a + \Delta\mu_b \cdot \rho_b \cdot x_b)} \quad \text{eq. (2)}$$

Thus, high sensitivity for detecting absorber **a** (threat object) against a background of absorber **b** (benign object) will be obtained when the differences in attenuation coefficient  $\Delta\mu$  obey the following relations:

$$|\Delta\mu_a| = \textit{maximal} \text{ and } |\Delta\mu_b| = \textit{minimal}$$

or, alternatively, if:

$$\Delta\mu_a, \Delta\mu_b \text{ have opposite signs}$$

(clearly also, the effect of any benign absorber **b** on this ratio cannot be fully eliminated unless  $\Delta\mu_b = 0$ ).

In order to illustrate the consequences of eq. (2), the compiled values for the quantity:

$$\Delta\mu = \mu(E_{\gamma\text{high}}) - \mu(E_{\gamma\text{low}} = 4.43 \text{ MeV})$$

are shown in Fig. 1 as function of atomic number **Z**, for several photon energies  $E_{\gamma\text{high}}$ . The choice of the lower energy  $E_{\gamma\text{low}} = 4.43 \text{ MeV}$  was dictated by the fact that it corresponds to the global minimum in attenuation coefficient  $\mu$  as function of energy, and also to a copiously-produceable  $^{12}\text{C}$  gamma-ray.

Fig. 1 shows that the  $\Delta\mu$  values are indeed small for medium-**Z** materials and even negative for low-**Z** materials. Moreover, the sensitivity to high-**Z** materials increases quite sharply with photon energy  $E_{\gamma\text{high}}$ . Thus it is desirable, on contrast-sensitivity grounds, to employ the highest photon energy  $E_{\gamma\text{high}}$  possible.

In order to illustrate the specificity of DER to SNM, as distinct from other high-**Z** materials, Fig. 2 shows  $\Delta\text{MAC}$ , the **difference in macroscopic attenuation coefficient**  $\Delta\mu \cdot \rho$  (where  $\rho$  is the bulk density) of high-**Z** material traversed, calculated for  $E_{\gamma\text{high}} = 15.09 \text{ MeV}$  and  $E_{\gamma\text{low}} = 4.43 \text{ MeV}$ . Such parametrization (see eq. (2)) is meaningful, since the volume distribution of  $\Delta\text{MAC}$  for suspect items can be estimated with adequate precision (in voxels of  $\sim 1 \text{ cm}^3$ ) from a small number of DER views(at least two).

Clearly, on the basis of the macroscopic attenuation, SNM (in Fig. 2, uranium and plutonium) can be readily distinguished from Rare-Earths and the heaviest stable elements (hafnium, thallium, lead and bismuth in Fig. 2) and to a lesser extent, from the transition metals (tantalum and mercury in Fig. 2). The only difficulty appears to be with the noble metals and their neighbours (tungsten, rhenium, osmium, iridium, platinum and gold in Fig. 2), but these are unlikely to be transported as undeclared cargo.

### Continuous-Spectrum And Discrete-Line Photon Sources For DER

Hitherto, most DER applications have employed *continuous-energy* spectra, such as those produced in electron-beam-induced Bremsstrahlung (BS) sources. However, in

the present application, working with BS-sources is not preferred due to two of their fundamental characteristics, namely:

I. the flux tends to be concentrated at low energies and tails off at high energies, thus reducing contrast

II. the low duty factor of typical BS beams ( $\sim 1\%$ ) is unfavorable for spectroscopy (single event counting)

Thus even though the present invention can be carried out with *continuous-energy* sources, nevertheless it is preferred to use *discrete-energy* nuclear-reaction-induced sources. Basic (although non-limiting) system requirements for DER are as follows:

- a. production of  $E_{\gamma\text{low}}$  and  $E_{\gamma\text{high}}$  in the same nuclear reaction
- b. clean gamma spectra (in the sense of containing as few other lines as possible)
- c. minimal neutron production and activation of environment
- d. populating reaction accessible with low-energy, low-intensity, non-exotic beams and durable targets
- e. robust, reliable, compact and low-cost accelerator
- f. reliable, low-cost detectors that resolve  $E_{\gamma\text{low}}$  from  $E_{\gamma\text{high}}$  and discriminate against interfering radiation

These requirements on nuclear-reaction-induced sources, as well as the paramount contrast-sensitivity criterion, that favors working with the highest possible gamma-ray energy  $E_{\gamma\text{high}}$ , serve as guidelines in selecting the most appropriate nuclear reactions for the present application. However, it is emphasized that the invention is not limited to these guidelines.

Initially, the nucleus in which the optimal levels and transitions are to be found may be identified. This is readily accomplished by considering the proton separation energies in light nuclei, or equivalently, the ground-state Q-values ( $Q_0$ ) for the  $(p,\gamma)$  proton-capture reaction. The latter represent a measure of the intrinsic exo-thermicity of the nuclear process (over and above the kinetic energy imparted by the incoming proton) and thus of the degree of excitation achievable in the final nucleus. Their systematics in light nuclei, taken from a well-known compilation, are shown in Fig. 3.

The global variations and local fluctuations in this plot represent a superposition of nuclear-shell closure effects (at the “magic” numbers), pairing-force effects (odd-even staggering in neighboring nuclei) and most prominently,  $\alpha$ -clustering effects (the dominant repetition pattern of maxima in  $Q_0$  is 4 mass units).

The highest excitations (two open diamonds on the left in Fig. 3) are obtained for  $p$ -capture on  $^3\text{H}$  and on  $^7\text{Li}$ . However, both these reactions are not preferred for the present application, since the cross-section (and gamma-yield) of the former is extremely low and the latter leads to  $^8\text{Be}$ , which breaks up into two  $\alpha$ -particles without emitting gamma-rays. The next best target nucleus (by far) is  $^{11}\text{B}$  (solid diamond just to the right of the above-mentioned open diamonds in Fig. 3). Thus the nucleus in which the highest excitations can be achieved is  $^{12}\text{C}$ , which is the product of the  $^{11}\text{B}(p,\gamma)$  reaction.

Populating the final nucleus at high excitation is a necessary but not sufficient condition for generating high-energy gamma-rays with low-energy particle beams. A further requirement is that the highly-excited levels may decay predominantly (or at least appreciably) to the ground-state or to low-lying excited states in a single transition. In general, this is not the case, because, at high excitation, when a nucleus has the possibility of decaying by particle emission (via the so-called “strong” nuclear force), its branching ratio for emitting gamma-rays (decay via the “electromagnetic” force) is usually rather small. However, for certain “pathological” states, quantum-mechanical selection rules can drastically inhibit particle emission. Such states will indeed decay appreciably via gamma emission. Classic examples of this are isospin  $T = 1$  states in self-conjugate ( $N=Z$ ) light nuclei, which are forbidden to decay via  $\alpha$ -particle emission. Since  $T$  is known to be a good quantum number in light nuclei, these selection rules can inhibit particle emission by many orders of magnitude, and in certain cases they do.

All these desirable properties are to be found in the  $^{12}\text{C}$  nucleus (which has  $N=Z=6$ ), the level scheme of which is presented in Fig. 4. The high-energy gamma-transitions in  $^{12}\text{C}$ , along with the 4.43 MeV transition, will constitute the first described embodiment of the present invention (see next section). Also shown in Fig. 4 are the low-lying levels of  $^{12}\text{B}$  and their decay modes, which will figure in another embodiment, described further hereinbelow.

### First Embodiment – In-Beam, Reaction-Induced $^{12}\text{C}$ $\gamma$ -Ray Yields

In the DER context, it is clear from Fig. 4 that the **4.43 MeV** gamma-ray is a prime candidate for  $E_{\gamma\text{low}}$ . With respect to  $E_{\gamma\text{high}}$ , the most attractive candidates are the discrete level at **15.09 MeV**, accessible via the following reactions  $^{11}\text{B}(\text{p},\gamma)$ ,  $^{11}\text{B}(\text{d},\text{n})$ ,  $^{10}\text{B}(^3\text{He},\text{p})$  and  $^{13}\text{C}(^3\text{He},\alpha)$  and the Giant Dipole Resonance (GDR) around **23 MeV** (accessible via  $^{11}\text{B}(\text{p},\gamma)$  at  $E_{\text{p}} = 6 - 10 \text{ MeV}$ ).

### Nuclear Reaction Yields

The expected thick-target gamma-ray yields (per projectile) of the **15.09 MeV** line and the GDR lines in the above-mentioned reactions were obtained by energy-integration of the published experimental cross-sections and are shown in Fig. 5.

Several comments on these reactions already appear in the caption to Fig. 5 and need not be repeated. Clearly, the choice of reaction defines an order-of-magnitude yield hierarchy: **p-capture** is the weakest (but the mean  $E_{\gamma\text{high}}$  is higher than **15.09 MeV**, thereby enhancing the contrast sensitivity) and  **$^3\text{He}$ -induced** processes are intermediate. **Deuteron-stripping** is the best, although its feeding of the **15.09 MeV** state has a threshold at  $E_{\text{d}} \sim 1.6 \text{ MeV}$ . At  $E_{\text{d}} \sim 3 \text{ MeV}$ , the yield of **15.09 MeV** gamma-rays is  **$\sim 3$  orders of magnitude** higher than the **9.17 MeV** yield in the Gamma-Resonance-Absorption (GRA) method underlying nitrogenous explosives detection. For those skilled in the art of security screening applications, this quantity probably best underscores the applicability of the present invention with the  $^{11}\text{B}(\text{d},\text{n})$  reaction. At energies above  $E_{\text{d}} \sim 3 \text{ MeV}$ , the thick-target **(d,n)** gamma yield will continue to rise approximately as  $E_{\text{d}}^{1.5}$ . This primarily reflects the deuteron range-dependence on energy, since the cross-sections are fairly flat. On the debit side, these reaction-induced gamma sources are characterized by relatively high associated fast-neutron yields, as illustrated by the following table:

**Table 1. Fast-neutron & 15.09 MeV  $\gamma$ -ray Thick-Target Yields and their ratios at selected energies**

Projectile + Target	$E_{\text{projectile}}$ [MeV]	15.09 MeV $\gamma$ -ray Yield	Fast-Neutron Yield	Neutrons/ $\gamma(15.09 \text{ MeV})$
<b>d + <math>^{11}\text{B}</math></b>	<b>3.0</b>	<b><math>4.5 \cdot 10^{-6} / \text{d}</math></b>	<b><math>\sim 2.3 \cdot 10^{-5} / \text{d}</math></b>	<b><math>\sim 5</math></b>
<b>d + <math>^{11}\text{B}</math></b>	<b>5.0</b>	<b><math>6.0 \cdot 10^{-6} / \text{d} *</math></b>	<b><math>&lt; 1.8 \cdot 10^{-5} / \text{d} *</math></b>	<b><math>&lt; 3 *</math></b>

$^3\text{He} + ^{13}\text{C}$	5.0	$3.0 \cdot 10^{-6} / ^3\text{He}$	$> 2 \cdot 10^{-5} / ^3\text{He}^{**}$	$> 7^{**}$
$^3\text{He} + ^{10}\text{B}$	5.3	$4.0 \cdot 10^{-7} / ^3\text{He}$	$> 4 \cdot 10^{-6} / ^3\text{He}^{**}$	$> 10^{**}$
$p + ^{11}\text{B}$	3.0	$\sim 1 \cdot 10^{-8} / p (\gamma_0 + \gamma_1)$	0 (below (p,n) threshold)	0
$p + ^{11}\text{B}$	3.5	$\sim 3 \cdot 10^{-8} / p (\gamma_0 + \gamma_1)$	$\sim 1 \cdot 10^{-5} / p$	$\sim 300$
$p + ^{11}\text{B}$	4.0	$\sim 4 \cdot 10^{-8} / p (\gamma_0 + \gamma_1)$	$\sim 3 \cdot 10^{-5} / p$	$\sim 800$
$p + ^{11}\text{B}$	6.0	$\sim 1.6 \cdot 10^{-7} / p (\gamma_0 + \gamma_1)$	$\sim 2.5 \cdot 10^{-4} / p$	$\sim 1500$
$p + ^{11}\text{B}$	9.0	$7.0 \cdot 10^{-7} / p (\gamma_0 + \gamma_1)$	$\sim 1.4 \cdot 10^{-3} / p$	$\sim 2000$

\* employing intermediately-thick target ( $\sim 4 \text{ mg/cm}^2$ ), which degrades deuteron beam energy down to 4 MeV

\*\* lower limits, since only ( $^3\text{He},n$ ) channel was taken into account, whereas ( $^3\text{He},pn$ ) was neglected (no data available)

The neutron yields in Table 1 were calculated in analogous fashion to the gamma-ray yields of Fig. 5, namely, by energy-integration of the published experimental cross-sections. It is clear from the results that ( $d,n$ ) has the edge over  $p$ -induced and  $^3\text{He}$ -induced reactions not only with respect to gamma-yield, but also in terms of minimizing the neutron/gamma yield ratio.

The unique exception to this trend is the  $p + ^{11}\text{B}$  system below the ( $p,n$ ) threshold at  $E_p=3.0 \text{ MeV}$ , but the gamma yields per projectile are almost three orders of magnitude lower than with  $d + ^{11}\text{B}$ . With increasing proton energy, the gamma-yields increase quite sharply, but the neutron yields increase even faster, so that the neutron/gamma ratios become unacceptably high, as can be seen from the table. For  $^3\text{He}$ -induced reactions, there is no bombarding energy at which the neutron/gamma yield ratio is minimized, since all gamma and neutron producing reactions are exothermic (no thresholds) and their cross-sections are essentially independent of energy. Finally, with the ( $d,n$ ) reaction, there appears to be a possibility of reducing the neutron/gamma ratio without sacrificing gamma yield, by raising the beam energy to  $E_d \sim 5 \text{ MeV}$  and employing a target of a thickness that does not degrade the beam below  $E_d \sim 4 \text{ MeV}$ . This may be due to a marked reduction in the ( $d,n$ ) cross-sections to the ground-state and first-excited-state of  $^{12}\text{C}$  in this energy range. Of course, such improvement might be at the expense of the 4.43 MeV gamma yield, which is undesirable. At higher deuteron energies the cross-section behavior is not known, so it is possible that even more favorable beam-target conditions might exist. However, this is unlikely, since at  $E_d \sim 6 \text{ MeV}$  the ( $d,2n$ ) channel opens.

The next topics to be considered are: a) whether the in-beam  $d + ^{11}\text{B}$  spectra are clean enough for the purposes of the present application and b) what measures can be

adopted to alleviate the adverse effects of the high neutron yield. These issues are discussed in the following paragraphs.

#### Experimental Options for Ensuring Clean In-Beam Gamma Spectra

In order to generate clean, background-free in-beam spectra, particularly with deuteron or  $^3\text{He}$  beams, certain experimental measures commonly implemented in nuclear spectroscopy may have to be taken. In this context, it is instructive to examine two published in-beam spectra. Fig. 6 displays a NaI gamma-ray spectrum with the  $^{11}\text{B}(\text{d},\text{n})$  reaction at an energy of  $E_d = 2.75 \text{ MeV}$  taken in the 1960's. Fig. 7 shows a spectrum taken in 2000 with "EUROBALL", a large Ge-spectrometer matrix surrounded by an array of NaI anti-coincidence counters. The latter employed the inverse reaction at a close center-of-mass energy.

Some features of these spectra relevant to the present application are:

- a. the **15.09 MeV** peak region is very clean in both cases
- b. the spectra are very similar for the two detectors
- c. the same characteristic continuum, extending up to **~10 MeV** equivalent  $\gamma$ -ray energy, is seen
- d. the **4.43 MeV** radiation is prominent
- e. in the NaI spectrum (Fig. 6), there are no other prominent peaks above **3.5 MeV**

The similarity of the NaI and Ge spectra, particularly with respect to the broad mid-spectrum bump, is a strong indication that this continuum is due to thermal-neutron capture in the detectors (which serve as "calorimeters" for the subsequent gamma cascades). The **3.09 MeV** line in Fig. 6 was identified as being due to the  $^{12}\text{C}(\text{d},\text{p})^{13}\text{C}$  reaction, stemming from a carbon impurity in the boron target - indeed, as evident from Fig. 7, it is not seen in the inverse reaction. (Thus, care may be taken to prepare as pure a  $^{11}\text{B}$  target as possible and to ensure that no carbon deposits accumulate on it during beam bombardment.) The source of the **5.5 MeV** peak in the Ge spectrum (Fig. 7) is unknown, but this is not directly relevant to the problematics of the present case, since the inverse reaction will not be employed in this application.

The above clearly shows that the primary sources of background under the **4.43 MeV** line are thermal-neutron-capture events and low-pulse-height response events to **15.09 MeV** gamma-rays. Measures that may be taken to alleviate the neutron-associated background problem are as follows:



1. using  $^{11}\text{B}$  target thicknesses that do not degrade the beam below the **15.09 MeV** threshold ( $E_d = 1.6 \text{ MeV}$ )
2. fast-neutron dumps up & downstream from target -  $^{11}\text{B}(\text{d},\text{n})$  neutrons are forward & backward-peaked
3. accordingly, locating the DER radiography system at angles around  $90^\circ$  to the deuteron beam
4. surrounding the target by neutron-moderators and absorbers
5. enveloping the detectors in a thermal-neutron-absorbing material, such as **Li, B** or **Cd**
6. employing organic scintillators as gamma-ray detectors
7. low-frequency pulsing of the deuteron beam (see the next embodiment)

**Measure #1** is explained in a paragraph further hereinbelow regarding targets – it should reduce neutron doses by  $\sim 30\%$ .

**Measures #2-5** are self-explanatory to the skilled artisan and will not be discussed further here. Each can be applied independently.

**Measure #6** is based on the favorable feature that low- $Z$  materials, such as organic scintillators, do not exhibit the thermal-neutron-capture feature characteristic of high- $Z$  detectors. In contrast, such detectors have the drawback of being efficient for detecting fast neutrons, primarily via proton recoil accompanying  $\text{n-p}$  scattering on hydrogen. Specifically, neutrons of energy around **10 MeV** will produce pulses equivalent to  $\sim 5 \text{ MeV}$  gamma-rays, thereby generating spectral background under the **4.43 MeV** region of interest. However, this problem may be solved by invoking the pulse-shape-discrimination (PSD) property of certain organic scintillators, that permits the distinction between fast-neutron and gamma-ray events in the detector via the difference in fall-time of the scintillation pulses. The PSD effect is most pronounced in liquids (where it gives rise to easily-detectable pulse-fall-time differences of **15-20 ns**) but has also been observed, albeit to a lesser extent, in plastic scintillators.

Once the fast and slow neutron-events have been suppressed, the principal spectral background under the **4.43 MeV** line may be due to low-amplitude **15.09 MeV** gamma-ray events. However, a response-optimized organic-scintillator may exhibit a flat background in the region of interest, that can be reliably subtracted from the **4.43 MeV** peak. In this context, one should also consider the use of deuterated scintillators, in which the **2.2 MeV**  $\gamma$ -ray from slow-neutron-capture by hydrogen is eliminated. It would permit

utilizing a higher fraction of the response curve to 4.43 MeV gamma-rays, thereby increasing the detector efficiency.

Employing organic scintillators might thus be advantageous (and also considerably cheaper), but may incur some loss in detection efficiency.

It is noted that different kinds of scintillators may be employed in the invention. For example, as mentioned before, the scintillators may be organic scintillators (e.g., organic liquid scintillators and/or organic plastic scintillators, with or without pulse-shape-discrimination properties. Alternatively, the detectors used may include inorganic scintillator spectrometers, such as but not limited to, NaI, BGO or BaF<sub>2</sub>. As another alternative, the detectors used may include solid-state radiation spectrometers, such as but not limited to, Ge, CdTe or CdZnTe (CZT). When employing organic scintillators without the pulse-shape discrimination feature, or alternatively, when using inorganic scintillators or solid-state radiation spectrometers, invoking one or more of measures #1-5 may in itself provide adequate discrimination against spectral contamination by fast or slow neutrons. This depends on the detailed experimental conditions prevalent in a specific application of the invention.

### **Implications Of $\gamma$ -Source For System Operating-Mode & Performance**

For the purpose of the discussion, a 2-dimensional schematic of the DER system embodiment is shown in Fig. 8. Its conventional aspects will not be elaborated on here, the emphasis being on features specific to this application. Fan beams and associated detector arrays are perpendicular to the plane of the drawing.

Fig. 8 explicitly cites the  $^{11}\text{B}(\text{d},\text{n})$  reaction, but would essentially be unchanged for p-capture or  $^3\text{He}$  reactions. Several features will now be discussed (accelerator and target issues are discussed further hereinbelow).

#### **Multi-view DER**

One of the features illustrated in Fig. 8 is that, using a number of collimator and detector arrays, a set of radiographic projections (views) of the screened object may be obtained simultaneously. This translates into a gain in system throughput, as well as facilitating the density reconstruction procedure, which permits discrimination against other, innocuous high-Z substances (see also hereinbelow).

Stringent collimation of the  $\gamma$ -beams to a fan geometry (perpendicular to the X-Y plane of Fig. 8) may be used to minimize the adverse effects of scattered radiation, a major problem with high-energy gamma-rays, especially traversing large, massive

objects. Such scattering will primarily tend to reduce contrast sensitivity, but it will also have the effect of blurring the image features (edges).

The DER object-screening sequence:

With the interrogating radiation produced by a nuclear reaction (as opposed to a Bremsstrahlung source), the low amounts of radiation available may be judiciously utilized, if the DER system is to achieve high throughput, high detection probability and low false-alarm rates.

The transmission sampling of the two  $\gamma$ -ray energies may be effected in identical irradiation geometry through any part of the interrogated object. Accordingly, the object-screening sequence may comprise one or more (in most cases, not more than two) of the following stages:

- I. a rapid pre-scan, to classify the overall  $\gamma$ -ray-attenuation general range
- II. a full scan with one detector array, to locate regions suspected of containing high-Z materials
- III. multi-view scans (Fig. 8), to establish presence of high-Z (along the lines previously described)
- IV. a localized scan with ultra-clean spectra (as mentioned above), to confirm presence of high-Z
- V. a repeat of one or more of the above stages in borderline cases, to eliminate persistent false-alarms

At stages I – III, the object will be scanned in continuous translational motion, possibly at variable speeds. Stage IV will only be implemented on the regions that proved problematic in the continuous scans.

In the DER system of the present invention, it may be feasible to subject all decision-making to computer control, with respect to: the specific scanning sequence to be performed, the mechanical motions required to execute it, as well as the data acquisition modes and analysis routines implemented for appraisal of the container status (“as yet undetermined”, “clean”, “suspect” or “bingo”) throughout its interrogation.

Projected performance characteristics:

By way of illustration, the projected performance characteristics are estimated for the  $^{11}\text{B}(\text{d},\text{n})$  reaction.

In-beam Gamma-ray yields from  $^{11}\text{B}(d,n)$ 

As can be read off Fig. 5, the **15.09 MeV  $\gamma$ -yield / deuteron** at  $E_d = 3 \text{ MeV}$  is  **$4.4 \cdot 10^{-6}$** . In this context, it is noteworthy that the anisotropy of the *in-beam* **15.09 MeV** gamma-rays has been measured and found to exhibit very slight peaking ( $\sim 10\%$ ) at  $90^\circ$  to the beam.

Thus, for a **200  $\mu\text{A}$ , 3 MeV d-beam** on a thick  $^{11}\text{B}$  target, the **15.09 MeV yield** is  **$5.3 \cdot 10^9 / \text{s}$** .

The **4.43 MeV** yields are slightly more difficult to estimate, since the  $^{12}\text{C}$  first excited state is populated directly in the **(d,n)** reaction with a typical **25 mb** cross-section (similar to that for the **15.09 MeV** state), but is also fed by gamma cascades from higher states. Judging by the spectra in Figs. 6 and 7 and the limited cross-section data available for the higher states, the **4.43 MeV** yield can be conservatively estimated as being *the same* as the **15.09 MeV yield** (in reality, it may be a factor of 2-3 higher).

Detector counting rates at full transmission (no absorber)

The counting rates are estimated assuming organic scintillator detector dimensions of  $1.5 \times 1.5 \times 40 \text{ cm}^3$ .

Detector solid angle ( $1.5 \times 1.5 \text{ cm}^2$  cross-section) at **400 cm** from target:  **$1.1 \cdot 10^{-6}$**

Total intrinsic efficiency (**40 cm length**):  **$\sim 0.50$**  at **15.09 MeV** and  **$\sim 0.69$**

at **4.43 MeV**

assumed useful response fraction:  **$\sim 0.3$**  at **15.09 MeV** and  **$\sim 0.2$**

at **4.43 MeV**

multiplying the latter two entries gives:

Useful intrinsic efficiency:  **$\sim 15\%$**  at **15.09 MeV** and  **$\sim 14\%$**

at **4.43 MeV**

Finally, taking **yield x detector-solid-angle x useful-intrinsic-efficiency** gives

Full-transmission counting rates of:  **$880 / \text{s}$**  at **15.09 MeV** and  **$810 / \text{s}$**

at **4.43 MeV**

In order to test the performance of the system in this counting-rate régime, detection and identification algorithms along the lines developed for GRA have been applied to synthetic images of an LD-3 aviation container and the expected probabilities of detection and false-alarm were determined. The simulations were performed for two different cargo contents:

### Cargo Content # I

LD-3 container, uniformly filled with low-Z (organic or aqueous cargo) equivalent to traversing 115 cm of water at every point in the scan (broadly representative of bulk agricultural produce, oil barrels, chemicals, etc.).

### Cargo Content # II

An iron slab of dimensions  $40 \times 15 \times 15 \text{ cm}^3$ , weighing **~70 kg** (representative of a heavy mechanical part).

Into each cargo type, a cube of SNM ( $1.5 \times 1.5 \times 1.5 \text{ cm}^3$  in dimensions) weighing **65 gr** was introduced.

For both these cases, 500 simulated DER scans of the container (each comprising two views at  $90^\circ$  orientation to each other) were generated using the counting-statistics/pixel corresponding to the calculated **4.43 MeV** and **15.09 MeV** transmission attenuations through the absorbers in question.

The preliminary analysis performed here follows a procedure along the lines of the one developed for explosives detection via GRA. The estimated DER performance characteristics presented here are based solely on the **detection and localization** of the suspicious object. Table 2 below presents the results of this simulation.

**Table 2: Simulation results**

<i>Cargo Content</i>	<i>Assumed Counts/pixel</i>	<i>Detection Probability</i>	<i>False-Alarm Rate</i>	<i>Scan-Time</i>
<b># I</b>	$N_{15}=120, N_4=30$	<b>&gt; 95%</b>	<b>&lt;1%</b>	<b>~3 min</b>
<b># II</b>	$N_{15}=150, N_4=150$	<b>&gt;99%</b>	<b>&lt;1%</b>	<b>~4 min</b>

where  $N_{15}$  and  $N_4$  are the assumed number of counts/pixel at the two energies detected after attenuation. The *Scan-Time* depends on the values assumed for  $N_{15}$  and  $N_4$ , on the number of slices (~130) that constitute a full scan of the entire container length and on the unattenuated counting rates quoted above.

It may be possible to enhance specificity to SNM by invoking criteria based on the object density, which is much higher for SNM than for high-Z materials such as Pb or Bi (see Fig. 2 and description above). To achieve such discrimination over voxels of typically  $1 \text{ cm}^3$ , a small number of radiographic views (2-6 or so) of the inspected object will suffice. Following Fig. 8, these could be taken in a single scan with multiple fan beams and detector arrays. It is thus possible to detect even smaller quantities of SNM

than the 65 gr cited above. However, even without this feature, the performance characteristics derived from the simulation are already very promising.

### Second Embodiment – Out-Of-Beam $^{12}\text{C}(4.43 \text{ MeV})$ Activation Yields

The second embodiment describes in detail **Measure #7** mentioned hereinabove, which is an option for scanning limited container regions with particularly clean gamma spectra, making use of in-beam prompt 15.09 MeV and out-of-beam delayed 4.43 MeV  $\gamma$ -rays. This option is based on the same  $^{11}\text{B} + \text{d}$  projectile-target system of the first embodiment, but via two different reaction channels.

The following is an explanation of the principal feeding and decay modes underlying the spectral lines observed in Figs. 6 and 7.

Apart from elastic scattering, the dominant nuclear reaction channels at incident energies  $E_d < \sim 5 \text{ MeV}$  are:

$$^{11}\text{B}(\text{d},\text{n})^{12}\text{C} \quad \text{and} \quad ^{11}\text{B}(\text{d},\text{p})^{12}\text{B} \text{ for which } T_{1/2} = 20.2 \text{ ms}$$

The cross-sections for both (d,n) and (d,p) reaction channels are typically 20-30 mb to each of the energetically-accessible states (including the  $^{12}\text{C}$  15.09 MeV state). They account for the intensities of the 0.95 & 1.67 MeV ( $^{12}\text{B}$ ), 4.43 & 15.09 MeV ( $^{12}\text{C}$ ) lines seen in the in-beam spectra of Figs. 6 and 7. One notable exception, however, is the cross-section for (d,p) to the  $^{12}\text{B}$  ground-state. There is a major discrepancy regarding its value, as appears in prior art literature, ranging from  $\sim 25 \text{ mb}$  in the  $E_d = 1.0\text{-}2.6 \text{ MeV}$  range, up to values 10-25 times higher (250 – 600 mb) at  $E_d = 2.6 \text{ MeV}$ . Another compilation, the EXFOR (CSISRS) database, quotes a cross-section of 176 mb at  $E_d = 3 \text{ MeV}$ , decreasing slowly with increasing deuteron energy. Since all excited  $^{12}\text{B}$  states decay to the ground-state within a fraction of a picosecond, the cumulative  $^{12}\text{B}$  production cross-section at each incident energy is the sum of the cross-sections to the individual excited states and the ground state. At  $E_d = 3 \text{ MeV}$ , four such excited states are energetically accessible (see Fig. 4). Assuming 25 mb to each excited state, the cumulative  $^{12}\text{B}$  production cross-section is thus, within the ground-state cross-section discrepancy limits, in the range 100 – 700 mb.

It is noted that the  $^{12}\text{B}$  ground state decays to the  $^{12}\text{C}(4.43 \text{ MeV})$  state with a branch intensity shown in Fig. 4 as 1.3% (the recently-adopted value is 1.23 (5) %). Thus, the  $^{11}\text{B}(\text{d},\text{p})^{12}\text{B}$  reaction can serve as a generator for 4.43 MeV activation gamma-rays, which may continue to be produced for a few tens of ms after the deuteron beam is switched off, until all  $^{12}\text{B}$  nuclei have decayed. These delayed 4.43 MeV gamma-rays are the basis for Measure #7 above.

The value of the  $^{12}\text{B}$  production cross-section may determine to a large extent whether the **4.43 MeV** yields are sufficient for the present application.

To illustrate this point, Table 3 shows the number of in-beam 15.09 MeV and out-of-beam 4.43 MeV activation gamma-rays produced in a thick  $^{11}\text{B}$  target by a 200  $\mu\text{A}$  beam of 3.0 MeV deuterons. They are respectively calculated for a 20 ms beam-burst, followed by 40 ms with no beam on target, assuming three different values for the  $^{12}\text{B}$  production cross-section, namely: **100 mb** (lower limit - column II), **250 mb** (intermediate value - column III) & **700 mb** (upper limit - column IV).

**Table 3: Number of gamma-rays produced in burst (parameter –  $^{12}\text{B}$  production cross-section)**

	$\sigma_{\text{prod}}(^{12}\text{B}) = 100 \text{ mb}$	$\sigma_{\text{prod}}(^{12}\text{B}) = 250 \text{ mb}$	$\sigma_{\text{prod}}(^{12}\text{B}) = 700 \text{ mb}$
Prompt 15.09 MeV: <i>beam on (20ms)</i>	Delayed 4.43 MeV: <i>beam off (40ms)</i>	Delayed 4.43 MeV: <i>beam off (40ms)</i>	Delayed 4.43 MeV: <i>beam off (40ms)</i>
$1.1 \cdot 10^8$	$3.2 \cdot 10^6$	$8.0 \cdot 10^6$	$2.2 \cdot 10^7$

Clearly, the *out-of-beam* spectra will be very clean, because there are no delayed gamma-rays at energies above **4.43 MeV**. Thus, invoking **measure #7** will furnish an option for measuring both relevant gamma-rays under background-free conditions - the **15.09 MeV** line *in-beam* and the **4.43 MeV** line *out of beam*. The latter are obviously isotropic, being emitted from unoriented nuclei.

However, as evident from Table 3, the *out-of-beam* yield of the **4.43 MeV** gamma-rays is at least a factor of **5** (and maybe even a factor of up to  $\sim 35$ , depending on the  $^{12}\text{B}$  production cross-section) lower than that of the *in-beam* **15.09 MeV** gamma-rays emitted during a single 20 ms beam burst.

**Counting-rate estimate: out-of-beam 4.43 MeV gamma-rays** (in analogy to the section on in-beam gamma-ray yields from  $^{11}\text{B}(\text{d},\text{n})$ )

Assume  $\sigma_{\text{prod}}(^{12}\text{B}) = 250 \text{ mb}$   $\gamma$  No. of **4.43 MeV**  $\gamma$ -rays in 40 ms for 200  $\mu\text{A}$  of 3 MeV d-beam =  **$8 \cdot 10^6$**

**Detector solid angle** ( $1.5 \times 1.5 \text{ cm}^2$  cross-section, 40 cm length) at 400 cm from target =  **$1.1 \cdot 10^{-6}$**

**Useful intrinsic efficiency:** (assuming useful response fraction of 30%)= **21%**

we obtain: **1.8 counts per (20+40) ms burst, or**

**30 /s**

Thus, within the uncertainty limits on  $\sigma_{\text{prod}}(^{12}\text{B})$ , we estimate:

**Full-transmission out-of-beam 4.43 MeV counting rates of:**

**12 - 84/s**

Thus, in view of the low counting rates expected for *out-of-beam* 4.43 MeV  $\gamma$ -rays, **measure #7** is likely to be exercised primarily if recourse to a localized scan with ultra-clean spectra (as mentioned above), to confirm the presence of high-Z is indeed required to resolve the issue. In such a case, the localized scan might be performed in *discrete stepping motion* of the container, the number of 60 ms (20 ms *beam-on* + 40 ms *beam-off*) cycles, or total time spent at each scan region being determined by the attenuation regime and counting statistics required. Ultimately, the entire process may be automated.

#### **Accelerator And Target Options**

Subject to the nuclear reaction chosen, one of the following beams may be used:

- a. **deuterons:** 100 - 300  $\mu\text{A}$  of 3 - 5 MeV
- b.  **$^3\text{He}$ :** 300 - 1000  $\mu\text{A}$  of 3 - 5 MeV
- c. **protons:** 500 - 1500  $\mu\text{A}$  of 9-10 MeV
- d. **mixed  $\text{d}^+$  &  $\text{H}_2^+$ :** 2000 - 5000  $\mu\text{A}$  of 3.5 MeV

**Options a, b & c** refer to reactions discussed in the section on Nuclear Reaction Yields, hereinabove, and will not be referred to further here.

**Option d** might provide a solution for a particular application that calls for detection of high-Z materials and nitrogenous explosives in a single system, or even in the very same scan. In the latter case, one could bombard a thin  $^{13}\text{C}$  layer deposited on the surface of a thick  $^{11}\text{B}$  target, with a mixed **mass = 2** beam of  $\text{H}_2^+$  (majority ion) and **deuterons** (minority ion). The  $\text{H}_2^+$  molecular ions, when they impinge on the  $^{13}\text{C}$  layer, will break up into two almost parallel, equal-energy protons at the **1.75 MeV** resonance, as required for a GRA explosives detection system. Having traversed the  $^{13}\text{C}$  layer, the protons will enter the  $^{11}\text{B}$  target, where they will contribute to high-energy gamma-ray production via the **p-capture** reaction (see Fig. 5). The **deuteron** component will traverse the  $^{13}\text{C}$  layer (contributing little in the way of reaction yield, the  $^{13}\text{C}$  being thin) and interact with the  $^{11}\text{B}$  target via the **(d,n)** reaction described above.



Alternately, should it be of interest to configure the high- $Z$  and explosives detection systems around the same accelerator without performing the scans simultaneously, a simpler variant of the above is feasible: one could accelerate **mass 2** to **3.5 MeV** in the machine, switching between hydrogen and deuterium in the ion source (and also changing the target) as required by the nature of the application at any given moment.

In terms of accelerator technology, **options a, b and c** may be realized with virtually any type of machine: cyclotron, radio-frequency-quadrupole (RFQ) or electrostatic (single-stage Van-De-Graaff or two-stage Tandem Van-De-Graaff). Beam current requirements are not excessive for any of these types. In contrast, **option d** would probably favor an RFQ, as GRA requires considerably higher beam currents.

Concerning targets, the requirements of the application are by no means excessive. High-quality and purity  $^{11}\text{B}$  layers (self-supporting, if necessary) have been produced by vacuum-deposition for many years. Moreover, beam-heating problems should not be severe, since boron has an extremely high melting point. As mentioned in the description of the first embodiment, one of the options for reducing the neutron background is to limit the target thickness so that, when the deuteron beam energy is degraded to below the **15.09 MeV** yield threshold (at  $E_d = 1.6 \text{ MeV}$ ), the beam emerges from the target and does not produce neutrons at lower bombarding energies. In practical terms, this means that the  $^{11}\text{B}$  layers may be made  $\sim 2 \text{ mg/cm}^2$  thinner than the full deuteron range in boron ( $\sim 5.5 \text{ mg/cm}^2$ , for  $E_d = 3 \text{ MeV}$ ). Doing so will suppress  $\sim 30\%$  of the neutrons one would get if the target were thick enough to stop the deuterons (**Measure #1** in the section concerning experimental options for ensuring clean in-beam gamma spectra).

The preference for the  $^{11}\text{B}(\text{d},\text{n})$  reaction (as mentioned in the description of the first embodiment) stems from its having the highest yield. However, an ultimate decision as to the optimal reaction may depend not only on its yield, but also on issues such as but not limited to, contrast-sensitivity, neutron doses to screened items and environment, accelerator complexity and cost, detector cost, etc. The accelerator considerations might eventually favor the  $\text{p-capture}$  and  $^3\text{He}$ -induced reactions over  $(\text{d},\text{n})$ , although higher beam currents will be needed to compensate for the lower reaction yields.

22  
CLAIMS

What is claimed is:

1. A method for detecting substances, the method comprising:  
performing multi-view, multi-energy radiography by irradiating an object with a plurality of discrete high-energy gamma-rays at a plurality of different orientations, and detecting and mapping radiation passing through the object with at least one array of detectors; and  
indicating a presence of a high- $Z$  substance by detecting a difference in a transmission attenuation characteristic of the high- $Z$  substance as opposed to low- $Z$  and medium- $Z$  substances.
2. The method according to claim 1, further comprising determining and localizing regions within said object containing the high- $Z$  substance with the multi-view, multi-energy radiography.
3. The method according to claim 1 or claim 2, further comprising determining and localizing regions within said object containing high-density substances with the multi-view, multi-energy radiography.
4. The method according to any of claims 1-3, wherein the high- $Z$  substance comprises a special nuclear material (SNM).
5. A system for detecting substances, the system comprising:  
a dual-energy radiography (DER) system comprising a gamma-ray radiation source, including a beam accelerator and a target to which said accelerator sends a beam thereby producing gamma rays, and a plurality of gamma ray detectors positioned to detect gamma ray beams that pass from the gamma-ray radiation source through an object to be inspected, wherein the DER system is adapted to indicate a presence of a high- $Z$  substance, by detecting a difference in a transmission attenuation characteristic of the high- $Z$  substance as opposed to low- $Z$  and medium- $Z$  substances.
6. The system according to claim 5, wherein said DER system is adapted to make two measurements of transmission attenuation characteristics, one measurement performed at the global absorption minimum for all atomic numbers  $Z$  (at  $\sim 4$  MeV photon energy) and another at a higher photon energy.
7. The system according to claim 6, wherein the global absorption minimum for all atomic numbers  $Z$  is approximately at 4 MeV photon energy.
8. The system according to any of claims 5-7, wherein the transmission attenuation characteristic of the high- $Z$  substance comprises a macroscopic attenuation coefficient

equal to the product of the specific attenuation coefficient and the bulk density of the high-Z substance.

9. The system according to any of claims 5-7, wherein said gamma-ray radiation source comprises a discrete-energy nuclear-reaction-induced source.

10. The system according to claim 9, wherein said nuclear-reaction-induced source has highly-excited levels that decay predominantly to a low-lying excited state in a single transition.

11. The system according to claim 9 or claim 10, wherein said nuclear-reaction-induced source has highly-excited levels that decay predominantly to the ground-state in a single transition.

12. The system according to any of claims 5-11, wherein said gamma-ray radiation source comprises at least one of the target and beam-projectile combinations  $^{11}\text{B}+\text{d}$ ,  $^{13}\text{C}+^3\text{He}$  and  $^{10}\text{B}+^3\text{He}$ , giving rise to nuclear reactions at beam energies  $E_{\text{beam}} < \sim 5 \text{ MeV}$ .

13. The system according to any of claims 5-12, wherein said gamma-ray radiation source comprises the  $^{11}\text{B}(\text{p},\gamma)$  reaction at a proton beam energy of  $E_p < \sim 9 \text{ MeV}$ .

14. The system according to any of claims 5-13, wherein said gamma-ray radiation source comprises the  $^{11}\text{B}(\text{d},\text{n})$  reaction, with a target thickness that does not degrade the beam below the  $15.09 \text{ MeV}$  threshold, wherein said threshold is at  $E_d \sim 1.6 \text{ MeV}$ .

15. The system according to any of claims 5-14, wherein said gamma-ray radiation source also emits  $^{11}\text{B}(\text{d},\text{n})$ , and  $^{11}\text{B}(\text{d},\text{n})$  neutrons that are forward and backward-peaked.

16. The system according to any of claims 5-15, wherein said DER system is positioned at angles around  $90^\circ$  to the beam.

17. The system according to any of claims 5-16, wherein said target is surrounded by at least one of neutron-moderators and absorbers.

18. The system according to any of claims 5-17, wherein the detectors are at least partially enveloped in a thermal-neutron-absorbing material.

19. The system according to any of claims 5-18, wherein said detectors comprise organic scintillators.


20. The system according to any of claims 5-19, wherein said detectors comprise organic liquid scintillators.

21. The system according to any of claims 5-19, wherein said detectors comprise organic plastic scintillators

22. The system according to any of claims 5-21, wherein said detectors comprise scintillators with pulse-shape-discrimination properties.

23. The system according to any of claims 5-18, wherein said detectors comprise inorganic scintillator spectrometers.
24. The system according to any of claims 5-18, wherein said detectors comprise solid-state radiation spectrometers.
25. The system according to any of claims 5-24, wherein said beam comprises a low-frequency pulsed deuteron beam.
26. The system according to any of claims 5-25, wherein said DER system emits a beam of mixed  $d^+$  and  $H_2^+$  ions at 3.5 MeV projectile energy, and wherein the DER system is adapted to indicate a presence of the high-Z substance and nitrogenous explosives as a function of the transmission attenuation characteristics of the high-Z substance and the nitrogenous explosives.
27. The system according to claim 26, wherein the DER system is adapted to indicate the presence of the high-Z substance and the nitrogenous explosives in the same beam scan.
28. The system according to claim 27, wherein the DER system is adapted to indicate the presence of the high-Z substance and the nitrogenous explosives by bombarding a thin  $^{13}C$  layer deposited on the surface of a thick  $^{11}B$  target, with a mixed mass comprising a beam of  $H_2^+$  and deuterons.
29. The system according to any of claims 5-27, wherein the DER system is adapted to switch between ion sources and to switch between targets.
30. The method according to any of claims 1-4, and substantially as shown and described hereinabove.
31. The system according to any of claims 5-29, and substantially as shown and described hereinabove.

For the Applicant,



David Klein, Patent Attorney  
Dekel Patent Ltd.

FIG. 1





FIG. 2







FIG. 3

FIG. 4






FIG. 6






FIG. 7




FIG. 8

